
I'm not robot  reCAPTCHA

[Continue](#)

Archivelog Activation

As I said, if its 10g then this parameter is not required and will have no effect.. All you need to do is "alter database archivelog" at mount stage, which you already have done.. Take note that you must supply the SID= option to the ALTER SYSTEM command The following statement will reset the above initialization parameter (removing it from the SPFILE): SQL> alter system reset log_archive_start scope=spfile sid='*'; Well, the solution is simple - simply reset the initialization parameter.. ORA-32006: LOG_ARCHIVE_START initialization parameter has been deprecated Hmm, looks like an issue.. Edit init ora and set log_archive_start=TRUE 3 Startup mount pfile=init ora 4 ALTER DATABASE ARCHIVELOG; 5.. Enable Archive Log Mode Can not backup open file in noarchivelog I have shutdown, mount and enabled archive mode Oracle says it is in archivelog mode.. When you enable this mode redo logs will be archived instead of overwritten The archivelogs are stored in a seperate place usually can backed up regularly by your standard filesystem backup system (NetBackup or whatever).. Archive logs are utilized by RMAN, Data Guard, Flashback and many others A standby database maintains a duplicate, or standby copy of your primary also known as production database and provides continued primary database availability in.. var q = 'archivelog%20activation'; Hi, I've tuned on the archive log mode already.

Enable the archivelog mode?ARCHIVELOG mode Any Oracle database that contains important data should be running in ARCHIVELOG mode.. I hope you followed the steps mentioned below to enable archiving 1 Shutdown db 2.. However the archiving will not persists on restarting the db Hence the 5-steps mentioned above is the way to go.. ALTER DATABASE ARCHIVELOG; 5 ALTER DATABASE OPEN The ALTER SYSTEM ARCHIVE LOG START; command will also start the archiving without having to re.. Most of the High Availability features of Oracle require you to enable ARCHIVELOG mode for your database.

But how can I find the redolog files Enabling ARCHIVELOG ModeOracle Archive Log Mode: Startup The Database In Archivelog Mode: Steps Required To Take A Database Not In Archive Log Mode And Alter It To Archive Log Mode.. However, the value of "log_archive_start" is FALSE After than I edit init ora change it to TRUE and shutdown DB, startup mount and then alter database open.. SQL alter database archivelog; Indicates whether the archivelog has been applied to its corresponding standby database YES ACTIVATION NUMBER: Number assigned to the database.. Take note that you must supply the SID= option to the ALTER SYSTEM command The following statement will reset the above initialization parameter (removing it from the SPFILE): SQL> alter system reset log_archive_start scope=spfile sid='*';How to Enable Archive Log mode.. So stop concentrating on that parameter Also, you might get the following error if you set "log_archive_start" parameter.

ALTER DATABASE OPEN The "ALTER SYSTEM ARCHIVE LOG START;" command will also start the archiving without having to re-start the db.. Give the following command to see the archiving status SQL>archive log list; SQL> archive log list; Database log mode Archive Mode Automatic archival Enabled Archive destination /home/oracle/OraHome1/dbs/arch Oldest online log sequence 5 Next log sequence to archive 7 Current log sequence 7 However, the value of "log_archive_start" is FALSE.. Which method did you follow ? Also are you using spfile? In that case you have to enable log_archive_start in spfile using the following command alter system set log_archive_start=true scope=spfile Execute the following command in order to test whether archiving is happening or not :- SQL>archive log all; Well, the solution is simple - simply reset the initialization parameter.. How come it is possible? Regards, Fan You did not tell me the version of oracle.. But the value of "log_archive_start" still "FALSE" What I have done wrong? And what is consequence if the value "FALSE"? What is your oracle version? If it's 10g then "log_archive_start" parameter is deprecated and is not required.. Archive log list; Database log mode No Archive Mode database in archive log mode.. Running in Archive log mode enables you to take I think that the archivelog files will be inside the directory defined together with the activation of the archivelog mode.

e10c415e6f